

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS


**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup>:</b> <b>A01B 71/08</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 94/19923</b> <b>(43) International Publication Date:</b> 15 September 1994 (15.09.94)
<b>(21) International Application Number:</b> PCT/EP94/00545 <b>(22) International Filing Date:</b> 24 February 1994 (24.02.94)  <b>(30) Priority Data:</b> 9304555.7      5 March 1993 (05.03.93)      GB  <b>(71)(72) Applicant and Inventor:</b> TAYLOR, William [GB/GB]; 55 Letterloan Road, Macosquin, Coleraine, Co. Londonderry BT51 4PP (GB).  <b>(74) Agent:</b> VINSOME, Rex, Martin; Dibb Lupton Broomhead, Fountain Precinct, Balm Green, Sheffield S1 1RZ (GB).		<b>(81) Designated States:</b> AU, CA, GB, NZ, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i> <i>With amended claims.</i>

**(54) Title:** GUARD ATTACHMENT FOR POWER TAKE-OFF SHAFT**(57) Abstract**

A guard attachment (1) for a wide-angled joint on a PTO shaft located between a prime mover and an accessory or implement comprises: a pair of flexible hollow cone-shaped members (10, 11) each capable of axial bending but resistant to radial compression, each cone-shaped member being provided at its narrower diameter end with a first connector means (14, 15), the first connector means either (a) being adapted to connect the cone-shaped member to a housing of the prime mover or of the accessory or implement; or (b) being adapted to connect the cone-shaped member to another PTO shaft guard attachment; or (c) comprising bearing means adapted to be locatable about a PTO output/input stub of a prime mover, implement or accessory and a second connector means (18, 19) adapted to connect the cone-shaped members together at their wider diameter ends.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

GUARD ATTACHMENT FOR POWER TAKE-OFF SHAFTTechnical Field

This invention relates to a guard attachment for a  
5 power take-off shaft between a prime mover and an  
accessory or implement, and more particularly to a guard  
attachment for a power take-off shaft comprising a wide-  
angled joint.

10 Background Art

The specification of my European Patent No. 0086606  
discloses a safety guard for a power take-off (PTO) shaft  
between a prime mover and a powered accessory or  
implement whose orientation with respect to the prime  
15 mover may change, the guard comprising a flexible tubular  
member capable of axial extension and retraction and of  
axial bending but resistant to radial compression,  
bearing means being provided within the flexible tubular  
member for engagement with the PTO shaft when the  
20 flexible tubular member undergoes axial bending.  
Coupling means are provided at each end of the flexible  
tubular member for attachment to housings of the prime  
mover and the accessory or implement.

In my European Patent Application No.92902512.0 I  
25 have disclosed a further arrangement in which a connector  
means for a PTO shaft guard comprises bearing means  
adapted to be locatable about a PTO output/input stub of  
a tractor, vehicle or implement. The entire disclosures

of the above European patent and application are incorporated herein by reference.

The above arrangements have been very successful in practice, but difficulties have been encountered in  
5 locating a guard around a common type of PTO shaft which is provided with a wide-angled joint (usually at the tractor end of the shaft). Such joints are relatively large in comparison to the diameter of the PTO shaft, and the extreme range of angular movement of the joint places  
10 unacceptable stresses on the guard region surrounding the joint which can lead to rupture and failure.

#### Disclosure of the Invention

It is an object of the present invention to provide  
15 a safety guard for a wide-angled joint on a PTO shaft located between a prime mover and a powered accessory or implement.

This object and various other useful features are achieved in accordance with the invention by the  
20 provision of a bi-conical guard attachment which can be assembled over the joint.

According to the invention there is provided a guard attachment for a wide-angled joint on a PTO shaft located between a prime mover and an accessory or  
25 implement which comprises:

a pair of flexible hollow cone-shaped members each capable of axial bending but resistant to radial compression,

each cone-shaped member being provided at its narrower diameter end with a first connector means, the first connector means either

(a) being adapted to connect the cone-shaped member  
5 to a housing of the prime mover, or of the accessory or implement, or

(b) being adapted to connect the cone-shaped member to another PTO shaft guard attachment, or

(c) comprising bearing means adapted to be  
10 locatable about a PTO output/input stub of a prime mover, implement or accessory

and a second connector means adapted to connect the cone-shaped members together at their wider diameter ends.

15 The prime mover can be, for example, an agricultural tractor, a lorry or truck, or similar vehicle. The accessory or implement can be for example, a powered harvester, a harrow, or similar powered equipment.

The cone-shaped members, which can be the same or  
20 different, can be formed from synthetic rubber or plastics materials, and are preferably of convoluted tubular construction, for example in the form of a pair of cone-shaped bellows which are capable of axial extension and retraction.

25 The cone-shaped members are preferably provided with internal support means which can, for example, be bearing rings which are preferably formed from a hard plastics material. The bearing rings are preferably contoured and

diametered so that they fit into the convolutions of the cone-shaped members. The guard attachment of the invention will normally be connected at one end to another elongate PTO shaft guard attachment which extends  
5 over the remaining exposed length of the PTO shaft, and at its other end either to a housing of the prime mover, accessory or attachment, or to a bearing means adapted to be locatable about the PTO output/input stub axle of the prime mover, accessory, or attachment. The connection to  
10 the elongate PTO shaft guard attachment is preferably of the quick attachment type, that is to say, not requiring separate bolts or screws, and may comprise, for example, a screw-threaded or a bayonet-type connector with male and female connecting parts. Examples of connections to  
15 housings are shown in my European Patent No. 0086606 and of connections to a bearing means in my European Patent Application No. 92902512.0. Preferably one of the cone-shaped members is provided with a first connector means which comprises one half of a bayonet connector for  
20 connecting to a cooperating part on an elongate PTO shaft guard attachment, and the other cone-shaped member is provided with a connector means for connection to a bearing means adapted to be locatable about a PTO output/input stub of a prime mover.

25 The second connector means for connecting the cone-shaped members together at their wider diameter ends can be a separate part, but is preferably located on one or both of the cone-shaped members. Preferably it is of the

quick attachment type, and for example it may comprise two cooperating parts, one on each of the cone-shaped members, which can be locked together. For example, the second connector means may comprise a bayonet-type  
5 connector or any other suitable device. In a preferred arrangement, the largest bearing ring of each cone-shaped member comprises one part of a two-part connector, and for example they may have male and female sections which can be locked together.

10 The guard attachment of the invention is easy to fit and remove at will and comprises relatively few parts of rugged construction. It provides a simple and inexpensive means of extending the versatility of the PTO shaft guard attachment of European Patent No. 0086606.

15 Various embodiments of the invention will now be specifically described with reference to the accompanying Drawings in which:

#### Brief Description of Drawings

20 Figure 1 shows a view of a PTO guard attachment of European Patent 0086606 in side elevation, together with a connector means of European Patent Application No. 92902512.0;

25 Figure 2 shows the PTO guard attachment of Figure 1 as applied to a PTO shaft incorporating a wide-angled joint, in side elevation;

Figure 3 shows an exploded view of a first guard attachment according to the invention; and



Figure 4 shows a side elevational view of the guard attachment of Figure 3 positioned on a PTO shaft and connected to the guard attachment of Figures 1 and 2.

5    Detailed Description of Drawings

Referring now to Figure 1, the prior art guard attachment illustrated generally at 1 comprises an elongate flexible convoluted tubular member 2, formed from synthetic rubber, having at each end a male part of  
10    a bayonet fitting 3,4 which are attachable respectively to female connectors 5,6 comprising a bearing adapted to fit over a stub axle.

Figure 2 shows the same guard attachment positioned on a PTO shaft 7, provided with a wide-angled joint 8.  
15    It can be seen that, solely to encompass the wide-angled joint it would be necessary to use a guard attachment far larger than would be necessary for the PTO shaft alone, and that the wide-angled joint is likely to represent a stress point for the convoluted tubular member.

20    Figure 3 shows an exploded view of a guard attachment according to the invention. The attachment, illustrated generally at 9, comprises a pair of convoluted cone-shaped bellows 10, 11 each having five convolutions. The outermost (narrowest) convolutions 12, 13 are provided with seated flanged bayonet connectors  
25    14, 15, which are respectively male and female. The innermost (widest) convolutions 16, 17 are provided with seated flanged bearing rings 18, 19 having cooperating

threaded portions 20, 21. The remaining convolutions are provided with seated bearing rings 22 whose cross-sectional shape is illustrated in the inset. The cross-section of the rings 22 is generally triangular in order  
5 that they can be accommodated snugly in the convolutions.

The convoluted cone-shaped bellows 10, 11 can have any suitable number of convolutions, but preferably there are at least four on each cone-shaped bellows. The number of convolutions on each bellow need not  
10 necessarily be the same, and for example left hand bellows 10 could have five convolutions and right hand bellows 11 could have six convolutions.

The cone-shaped bellows can, for example have an internal diameter of about 160mm at the narrower end and  
15 about 245mm at the wider end. The convolutions can for example have a height of about 32.5mm, measured at the longer side, and a pitch of about 20mm.

Figure 4 shows a guard attachment assembled around a wide-angled joint on a PTO shaft. In assembling the  
20 guard attachment, the bellows 11 is first slid along the shaft and mated with the bellows 10 applied from the other end, via threaded bearing rings 18, 19. The elongate guard attachment 1 is then slid over the shaft and connected to the bellows 11 by the bayonet connector  
25 3, 15. There is thereby formed a continuous guard surface for the full length of the PTO shaft.

The reader's attention is directed to all papers and documents which are filed concurrently with this

specification and which are open to public inspection with this specification, and the contents of all such papers and documents are incorporated herein by reference.

5 All the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps or any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features  
10 and/or steps are mutually exclusive.

Each feature disclosed in this specification (including any accompanying claims, abstract and drawings), may be replaced by alternative features serving the same, equivalent or similar purpose, unless  
15 expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example only of a generic series of equivalent or similar features.

## CLAIMS

1. A guard attachment for a wide-angled joint on a PTO shaft located between a prime mover and an accessory or implement which comprises:
  - a pair of flexible hollow cone-shaped members each capable of axial bending but resistant to radial compression;  
each cone-shaped member being provided at its narrower diameter end with a first connector means, the first connector means either
    - (a) being adapted to connect the cone-shaped member to a housing of the prime mover or of the accessory or implement, or
    - (b) being adapted to connect the cone-shaped member to another PTO shaft guard attachment, or
    - (c) comprising bearing means adapted to be locatable about a PTO output/input stub of a prime mover, implement or accessory
  - and a second connector means adapted to connect the cone-shaped members together at their wider diameter ends.
2. A guard attachment according to Claim 1, in which the prime mover is an agricultural tractor.
3. A guard attachment according to Claim 1 or 2, in which the cone-shaped members are of convoluted tubular construction.

4. A guard attachment according to any of the preceding claims, in which the cone-shaped members are provided with internal support means.
5. A guard attachment according to Claim 4, in which the internal support means comprises a plurality of bearing rings.
6. A guard attachment according to Claim 5, in which the bearing rings are contoured and diametered so that they fit into convolutions on the cone-shaped members.
7. A guard attachment according to any of the preceding claims, in which the first connector means comprises a male or female part of a bayonet connector.
8. A guard attachment according to any of the preceding claims, in which the second connector means comprises two cooperating parts, one on each of the cone-shaped members.
9. A guard attachment according to Claim 8, in which each of the two cooperating parts also comprises the largest bearing ring of each cone-shaped member.
10. A PTO shaft having a wide-angled joint protected by a guard attachment according to any of the preceding claims.
11. A PTO shaft according to Claim 10, that is protected by a combination of a guard attachment according to any of Claims 1 to 9 covering the wide-angled joint, and a guard attachment of uniform diameter covering the remaining length of the PTO shaft, the two guard

attachments being connected by a quick attachment type connector.

12. A guard attachment for a wide-angled joint on a PTO shaft located between a prime mover and an accessory  
5 or implement, the guard attachment substantially as hereinbefore described with reference to the accompanying drawings.
13. A PTO shaft having a wide-angled joint protected by a guard attachment, substantially as hereinbefore  
10 described with reference to the accompanying drawings.

## AMENDED CLAIMS

[received by the International Bureau on 23 August 1994 (23.08.94); original claim 3 cancelled; original claim 1 amended; claims 4-13 renumbered as claims 3-12; other claims unchanged (3 pages)]

1. A guard attachment for a wide-angled joint on a PTO shaft located between a prime mover and an accessory  
5 or implement which comprises:  
a pair of flexible hollow cone-shaped members of convoluted tubular construction, each capable of axial bending but resistant to radial compression;  
each cone-shaped member being provided at  
10 its narrower diameter end with a first connector means, the first connector means either
  - (a) being adapted to connect the cone-shaped member to a housing of the prime mover or of the accessory or implement, or
  - 15 (b) being adapted to connect the cone-shaped member to another PTO shaft guard attachment, or
  - (c) comprising bearing means adapted to be locatable about a PTO output/input stub of a prime mover, implement or accessory  
20 and a second connector means adapted to connect the cone-shaped members together at their wider diameter ends.
2. A guard attachment according to Claim 1, in which the prime mover is an agricultural tractor.
- 25 3. A guard attachment according to any of the preceding claims, in which the cone-shaped members are provided with internal support means.

4. A guard attachment according to Claim 3, in which the internal support means comprises a plurality of bearing rings.
5. A guard attachment according to Claim 4, in which the bearing rings are contoured and diametered so that they fit into convolutions on the cone-shaped members.
6. A guard attachment according to any of the preceding claims, in which the first connector means comprises a male or female part of a bayonet connector.
7. A guard attachment according to any of the preceding claims, in which the second connector means comprises two cooperating parts, one on each of the cone-shaped members.
8. A guard attachment according to Claim 7, in which each of the two cooperating parts also comprises the largest bearing ring of each cone-shaped member.
9. A PTO shaft having a wide-angled joint protected by a guard attachment according to any of the preceding claims.
10. A PTO shaft according to Claim 9, that is protected by a combination of a guard attachment according to any of Claims 1 to 8 covering the wide-angled joint, and a guard attachment of uniform diameter covering the remaining length of the PTO shaft, the two guard attachments being connected by a quick attachment type connector.



11. A guard attachment for a wide-angled joint on a PTO shaft located between a prime mover and an accessory or implement, the guard attachment substantially as hereinbefore described with reference to the accompanying drawings.
- 5
12. A PTO shaft having a wide-angled joint protected by a guard attachment, substantially as hereinbefore described with reference to the accompanying drawings.

10

FIG. 1 (PRIOR ART)







FIG. 2 (PRIOR ART)







# INTERNATIONAL SEARCH REPORT

Intern. J Application No  
PCT/EP 94/00545

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 5 A01B71/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 5 A01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR,A,2 342 630 (WALTERSCHEID) 30 September 1977 see page 1, line 20 - line 30 see page 2, line 35 - page 3, line 8 see page 3, line 19 - line 28; figures	1-5,8-13
Y	---	6,7
Y	EP,A,0 086 606 (TAYLOR) 24 August 1983 cited in the application see abstract see page 3, line 16 - line 23	6
Y	WO,A,92 09189 (TAYLOR) 11 June 1992 see abstract; figures	7
X	FR,A,1 126 151 (PULLMAN) 16 November 1956 see the whole document	1-4,8, 11-13

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

9 June 1994

Date of mailing of the international search report

18. 07. 94

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Walvoort, B

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat'l Application No

PCT/EP 94/00545

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-A-2342630	30-09-77	DE-A- 2609069	01-09-77
		AT-B- 344431	25-07-78
		AU-A- 2066876	22-06-78
		CA-A- 1032977	13-06-78
		GB-A- 1570315	25-06-80
		JP-A- 52107460	09-09-77
		SE-A- 7614431	06-09-77
		US-A- 4107952	22-08-78
EP-A-0086606	24-08-83	AU-B- 552749	19-06-86
		AU-A- 1111883	11-08-83
		CA-A- 1203095	15-04-86
		US-A- 4663984	12-05-87
WO-A-9209189	11-06-92	AU-A- 8912791	25-06-92
		CA-A- 2095845	23-05-92
		EP-A- 0558678	08-09-93
		FI-A- 932319	21-05-93
		NZ-A- 240692	27-04-94
FR-A-1126151		NONE	